

VASTRAJET ELITE

1.8 Mtr Direct To Fabric Printer

With a Massive Production Capacity of 3200 sqm/day



SPECIFICATIONS

VASTRAJET ELITE						
CONFIGURATION			CC4044	CC4084	CC6064	CC8084
Printing Technology			Drop-on-demand, Piezoelectric Inkjet			
No. of Print Heads			4	8 (Dual Row)	6	8
Print Heads	Type	Industrial Grade Jetting Assemblies				
	Resolution	Upto 1440 DPI				
	Height Adjustment	Upto 10 mm				
	Cleaning Method	Pressure Purge and Wiping				
	Wetting Control	Piezoelectric Actuations				
Ink	Type	Pigment/Disperse/Reactive/Acid				
	No of colors		4	4	6	8
	Supply	3.9 Ltr, bulk ink supply system with inline degassing				
Fabric	Type	Cotton, Viscose, Polyester, Polyamide, Silk, Wool				
	Max. Thickness	Upto 5 mm				
	Fabric Width	1850 mm				
	Printing Width	Upto 1800 mm				
		Roll Diameter	Upto 450 mm			
Fabric Drying System			Infrared Heaters			
Operating Interface			Touch Screen			
Printing Interface			High Speed USB 2.0			
RIP Software Supported			RIP Master or NeoStampa (ColorJet Edition)			
File Format			JPEG / TIFF / BMP / PDF (RGB / CMYK)			
Power Supply			220 V, 8 KW Single / Three phase load distribution, 50Hz			
Operating Condition			Temperature: 24°C ± 4 Humidity: 60% ± 5% RH			
Outer Dimension/Weight			1500 x 3950 x 1400 mm (LxWxH) / 1050 kgs Approx.			
Speed (In Sq. Meter/Hrs)	Print DPI	Passes	CC4044	CC4084	CC6064	CC8084
For Reactive/Disperse/Acid						
Mode 1	540 x 720	2	87	161	87	87
Mode 2	540 x 1080	3	59	98	59	59
Mode 3	540 x 1440	4	43	75	43	43
For Pigment Ink						
Mode 4	720 x 720	4	35	65	35	35
Mode 5	720 x 1080	6	23	38	23	23
Mode 6	720 x 1440	8	18	31	18	18

Efficiency Guaranteed.
VASTRAJET Elite

