

SOFT SIGNAGE

SOFTJET GRAND®

8 COLOR
OPTION AVAILABLE

GRAND FORMAT 3.2 MTR. SOFT SIGNAGE PRINTER

FOR REDUCED ENVIRONMENTAL IMPACT & GREATER PROFITABILITY



SOFTJET GRAND, the 3.2 mtr wide printer is the perfect solution, completely in-sync with the diverse requirements of today's well-developed market. An industrial soft signage printer that combines digital advantages, efficiently optimised to replace PVC-based media completely. It easily prints on polyester-based fabrics which can be recycled and uses environment-friendly aqueous based inks. **Softjet Grand** is most suitable for a large range of soft signage applications, such as banners, displays, wall decorations, signage, parasols, flags, backdrops and outdoor advertisements.

- Ultra High Productivity
- Reduced Environmental Impact
- Vibrant Colors & Reproduction
- Maximum Applications & Profitability



BACKLIT BOARDS

FLAGS

CANOPY

DROP DOWN BANNERS

SPECIFICATIONS

			SOFTJET GRAND	
Models			L8424	L8824
Printing Technology			Drop on demand, Piezo electric inkjet	
Print Heads			Industrial Grade Jetting Assemblies	
No. of Print Heads			8	8
Fabric	Width	3300 mm		
	Thickness	Maximum 10mm with Liner		
	Roll Outer Diameter	Maximum 300mm		
	Roll Weight	Maximum 90kg		
	Core Diameter	76.2mm		
Types			Polyester, Satin, Canvas & Blends	
Printing Width			Maximum 3200mm	
Inks	Types	Direct disperse inks		
	Colors	4	8	
Printing Resolution (dots per inch)			Maximum Up to 1440 dpi	
Distance Accuracy			Error of less than ±0.3 % of distance travelled, or ±0.3 mm, whichever is greater	
Media Heating System			Pre-heater and post-heater, setting range for the preset temperature: 30°C to 60°C Dryer setting range for the preset temperature: 30°C to 60°C	
Connectivity			High Speed USB	
Power Requirements			AC 220 V, 40A(± 10%), 50Hz	
Dimensions (Printer only) (LxWxH)			5300 x 1450 x 1650mm	
RIP Software			PhotoPrint (ColorJet Edition)	
Weight (approx. with stand)			2000 Kgs	
Environmental	Power ON	Temperature: 18°C to 28°C. Humidity: 35% to 80%RH (non-condensing)		
	Power OFF	Temperature: 5°C to 40°C. Humidity: 20% to 80%RH (non-condensing)		
Print Speed (Sqm/hr)				
Modes	Print DPI	Passes	L8424	L8824
Mode 1	540 x 720	2	167	98
Mode 2	540 x 1080	3	116	68
Mode 3	540 x 1440	4	87	51
Mode 4	720 x 1080	6	46	26
Mode 5	720 x 1440	8	42	24
Fusing Unit Specification	Power Requirement	Voltage AC 380 V ± 10%, 50-60 Hz, 21A,		
	Heating Range	160°C- 240°C Heat Energy		
	Dimensions	5180mm x 900mm x 1540mm (LxWxH)		
	Max Fabric Width	3300 mm		



For Softjet Grand
Scan Here